

SHAR-AIR is the traditional towel warmer suitable for any room. The semioval main-

pipes and the tubes with a diameter of 15 mm are repeated at different rates, forming

harmonious balance and wide range of thermal outputs.


DIMENSIONS

Width 50 / 60 cm

Height 94,5/105,5/122/124,5/144,5/162/182/183,5/184,5 cm

Depth 3 cm


Depth from wall 10 cm



SHAR-AIR
95-50




SHAR-AIR
125-50




SHAR-AIR
162-50




SHAR-AIR
184-..




SHAR-A2R
122-50



SHAR-A2R
162-50



SHAR-A2R
182-..



SHAR-A3R
105-50



SHAR-A3R
145-50



SHAR-A3R
183-..



MODEL	HL cm	Standard white sablé SB 9016 €	EN 442			▲ ▽ t.c. cm	Height H cm	Width L cm	Weight M Kg	Volume V dm ³	DUAL FUEL VERSION with E.H.E. and sleeve	
			Δt 50K watt	Δt 40K watt	Δt 30K watt						Watt	€
SHAR-AIR	95-50	536,70	301	225	155	38	94,5	50	5	2,4	300	126,20
SHAR-AIR	125-50	585,30	387	289	199	38	124,5	50	6,3	3	400	127,40
SHAR-AIR	162-50	684,90	493	369	253	38	162	50	7,9	3,8	500	129,60
SHAR-AIR	184-50	722,50	558	417	287	38	184,5	50	8,9	4,3	500	129,60
SHAR AIR	184-60	750,50	636	476	327	48	184,5	60	9,9	4,7	650	131,80
SHAR-A2R	122-50	665,30	498	373	256	38	122	50	7,6	3,5	500	129,60
SHAR-A2R	162-50	796,70	647	484	333	38	162	50	9,7	4,5	650	131,80
SHAR-A2R	182-50	853,10	721	539	371	38	182	50	10,8	5	800	136,60
SHAR-A2R	182-60	905,70	837	626	430	48	182	60	12,3	5,6	900	140,20
SHAR-A3R	105-50	639,90	479	358	246	38	105,5	50	7,2	3,3	500	129,60
SHAR-A3R	145-50	786,80	639	478	328	38	144,5	50	9,5	4,3	650	131,80
SHAR-A3R	183-50	945,40	799	598	411	38	183,5	50	11,7	5,4	800	136,60
SHAR-A3R	183-60	1008,60	932	697	479	48	183,5	60	13,4	6,1	900	140,20

Thermostats p.228-229

STANDARD PRODUCTION

White sablé SB9016 paintwork, B70 brackets
Tolerance ± 3mm - Air vent ø 1/8"

MAXIMUM OPERATING PRESSURE 8 BAR

PRODUCTION ON REQUEST

Paintwork to BREM color list with
colored B70 brackets

Electric version e.Shar-AIR page 258


+15/25%

STANDARD FITTINGS

REG ø 1/2"


Feet and dividers, page 202

Special fittings, page 279




TAPPING CENTRES



REG fittings with reverse valves as standard
SHAR-AIR



SHAR-A2R



SHAR-A3R



FIXINGS
Brackets B70 included



SHAR-AIR 162-50


SHAR-A2R 162-50

SHAR-A3R 183-50

RECOMMENDED VALVES

CHROME VALVES KIT with:

- n°2 Valves with tailpieces
- n°2 Fittings (multilayer ø 16, copper ø 12, 14)
- n°2 Chrome wall plates ø 48, hole ø 16




KIT REVERSE VALVES TON
page 269

Art. KVR 137,10€



KIT REVERSE VALVES CYL with thermostatic option
page 273
Extra for BREM color list

Art. KCR 149,90€
53,40€



KIT REVERSE VALVES TON with THERMOSTATIC
Head page 269

Art. KTR 190,30€

SPECIAL FINISHES

page 267
Finishes Gold, Bronze, Brushed Nickel for 2 valves
Brushed Nickel FITTING KIT extra Art. RN 30,50€

REMOTE FITTINGS

Art. REM 42,10€
Tapping centres: at the rear of radiator ▲▽L - 16cm
DISTANT Valves page 274

